


Solid carbide ball nose end mills - Ballcut 270°
VHM - Radiusfräser - Ballcut 270°
Fraises a rayon carbure - Ballcut 270°
Karbür Küre Freze - Ballcut 270°



F	S	1000	R	2	C	22	A	50	N	072
END MILL	MG-10		DIN 6528						nACo Multilayer	
TYPE	QUALITY	DIAMETER	NORM	FLUTES	SHAFT TYPE	FLUTE LENGTH	HELICAL	RADIUS	COATED	FULL LENGTH

d1(e8)	L2	L3	L4	L1	d2(h6)	Z	R	Coated Code	Price (Euro)
3	2,56	2,5	9	57	6	2	1,50	FS0300R2C09A15N057	
4	3,41	3,3	12	57	6	2	2,00	FS0400R2C12A20N057	
5	4,27	4,1	15	57	6	2	2,50	FS0500R2C15A25N057	
6	5,12	4,7	18	57	6	2	3,00	FS0600R2C18A30N057	
8	6,83	6,5	19	63	8	2	4,00	FS0800R2C19A40N063	
10	8,54	8,2	22	72	10	2	5,00	FS1000R2C22A50N072	
12	10,24	9,8	26	83	12	2	6,00	FS1200R2C26A60N083	
16	13,66	13,4	32	92	16	2	8,00	FS1600R2C32A80N092	
3	2,56	2,3	30	100	6	2	1,50	FS0300R2C30A15N100	
4	3,41	3,3	36	100	6	2	2,00	FS0400R2C36A20N100	
5	4,27	4,1	40	100	6	2	2,50	FS0500R2C40A25N100	
6	5,12	4,7	45	100	6	2	3,00	FS0600R2C45A30N100	
8	6,83	6,5	48	100	8	2	4,00	FS0800R2C48A40N100	
10	8,54	8,2	52	100	10	2	5,00	FS1000R2C52A50N100	
12	10,24	9,8	60	130	12	2	6,00	FS1200R2C60A60N130	
16	13,66	13,4	70	130	13	2	8,00	FS1600R2C70A80N160	

				HRC <20			HRC <25			HRC <30			HRC <35			HRC <40			HRC <45			HRC <50			HRC <52		
$a_p=0,3 \times d1$ $de=d1 \times \cos \alpha$ $\sin \alpha= \frac{d1-2 \times a_p}{d1}$				1.7131-1.7139 1.7149-1.7262			1.4112 - 1.4116 1.4117 - 1.4125			1.7039 - 1.7225 1.7220 - 1.7226			1.5864 - 1.7707 1.6580 - 1.4542			1.7139 - 1.7262 1.7311 - 1.7323			1.8509 - 1.2713 1.2714 - 1.2718			1.2718 - 1.2726 1.2343 - 1.2344			1.2360 - 1.2782 1.2884 - 1.2365		
				Vc= 150 m/dk.			Vc= 140 m/dk.			Vc= 130m/dk.			Vc= 125 m/dk.			Vc= 120m/dk.			Vc= 110 m/dk.			Vc= 100m/dk.			Vc= 90 m/dk.		
d1	de	ap	β	fz	n	Vf	fz	n	Vf	fz	n	Vf	fz	n	Vf	fz	n	Vf	fz	n	Vf	fz	n	Vf	fz	n	Vf
4	3,67	1,2	18,5°	0,041	13016	540xZ	0,041	12149	500xZ	0,041	11280	460xZ	0,039	10847	420xZ	0,035	10413	360xZ	0,034	9545	320xZ	0,032	8678	280xZ	0,031	7810	240xZ
5	4,58	1,5	18,5°	0,052	10430	540xZ	0,051	9735	500xZ	0,051	9039	460xZ	0,048	8692	420xZ	0,043	8344	360xZ	0,042	7649	320xZ	0,040	6954	280xZ	0,038	6258	240xZ
6	5,50	1,8	18,5°	0,062	8685	540xZ	0,062	8106	500xZ	0,061	7527	460xZ	0,058	7238	420xZ	0,052	6948	360xZ	0,050	6369	320xZ	0,048	5791	280xZ	0,046	5211	240xZ
8	7,33	2,4	18,5°	0,083	6517	540xZ	0,082	6083	500xZ	0,081	5648	460xZ	0,077	5431	420xZ	0,069	5214	360xZ	0,067	4779	320xZ	0,064	4345	280xZ	0,061	3910	240xZ
10	9,16	3,0	18,5°	0,103	5215	540xZ	0,103	4867	500xZ	0,102	4520	460xZ	0,097	4346	420xZ	0,086	4172	360xZ	0,084	3824	320xZ	0,080	3477	280xZ	0,077	3129	240xZ
12	11,00	3,6	18,5°	0,124	4343	540xZ	0,123	4053	500xZ	0,122	3764	460xZ	0,116	3619	420xZ	0,103	3474	360xZ	0,100	3185	320xZ	0,097	2895	280xZ	0,092	2605	240xZ
14	12,83	4,2	18,5°	0,145	3723	540xZ	0,144	3475	500xZ	0,142	3227	460xZ	0,135	3103	420xZ	0,121	2978	360xZ	0,117	2730	320xZ	0,113	2482	280xZ	0,107	2234	240xZ
16	14,66	4,8	18,5°	0,166	3258	540xZ	0,164	3041	500xZ	0,163	2824	460xZ	0,155	2715	420xZ	0,138	2607	360xZ	0,134	2390	320xZ	0,129	2172	280xZ	0,123	1955	240xZ
18	16,50	5,4	18,5°	0,186	2895	540xZ	0,185	2702	500xZ	0,183	2509	460xZ	0,174	2413	420xZ	0,155	2316	360xZ	0,151	2123	320xZ	0,145	1930	280xZ	0,138	1737	240xZ
20	18,33	6,0	18,5°	0,207	2606	540xZ	0,205	2432	500xZ	0,203	2258	460xZ	0,193	2172	420xZ	0,173	2085	360xZ	0,167	1911	320xZ	0,161	1738	280xZ	0,153	1564	240xZ